

## LED Continuous Panel Light 50w



LED Continuous Panel Light - EFX-SHPLP50WCR

## LED Continuous Panel Light - EFX-SHPLP50WCR

Eco-FX LED Panel Light has super bright LED light source, which is stable and has no UV & IR emission.

Eco-FX LED Panel Light is powered by low voltage constant current driver, which provides a soft light, energy saving capabilities, long luminaire life and uniform light distribution.

Eco-FX LED Panel Light is the ideal replacement for traditional grid lights and fluorescent tubes. The anodized aluminium frame provides a stylish and fashionable look with no colour deterioration. Connectable up 1000 meters.

Dimensions	Photometric Data
	-90 0 90 90 90 90 90 90 90 90 90 90 90 90

EFX-SHPLP50WCR **Product Code** Size 1450mm x 150mm x 10mm Beam Angle 110° Input Voltage 100-240Vac 50/60 Hz Frequency Transformer Output 50W 33Vdc 1400mA **Running Current** Power Factor 0.95 Chip Set Epistar SMD 2835 95% Efficiency (LOR) Colour Temperature

Pure White 6000k
Warm White 3000k
Cool White 4000k

Lumen
Warm White 3900lm
Pure White 4100lm
Cool White 4000lm

Efficacy
Warm White 78I/w
Pure White 82I/w
Cool White 80I/w
Warm White >80

Technical 50w

LED Life 50,000Hrs

Operating Temperature -40° / +40°

IP Rating 20

Weight

w: www.eco-fx.co.uk

4kg

-80%
energy

EPISTAR ROHS