

)ownlight 5w



LED Downlight - EFX-RAMDL5W

LED Downlight 5w - EFX-RAMDL5W

The Eco-FX LED Downlight offers high luminosity COB LEDs giving efficient heat dissapation and produces a softer light. The long life driver offers constant current and voltage.

Dimensions:



Photometric:

	H (m)	D (m)	E (Ix)
60 60		40°	
	0.5	0.306	7166
	1.0	0.612	1792
V THA VI	1.5	0.918	796.3
30 30	2.0	1.224	447.9
	2.5	1.530	286.7

Product Code

Size

Beam Angle

Input Voltage

Frequency

Transformer Output

Running Current

Power Factor

Chip Set

Efficiency (LOR)

Colour Temperature

Lumen

Efficacy

CRI

LED Life

Operating Temperature

IP Rating

Cut Out

Technical 5w

EFX-RAMDL5W

Ø85mm x 115mm

40°

110-265Vac

50/60 Hz

5W 12.2VDC

350mA

0.93

Bridgelux

95%

Warm White 3000k

Warm White 400lm

80lm/w

Warm White >85+

50,000Hrs

-40° / +50°

20

Ø76mm















Eco-FX Limited Office 1, 192 Shoreham Street Sheffield S1 4SQ, UK

t: +44 (0) 114 321 9610 e: enquiries@eco-fx.co.uk

w: www.eco-fx.co.uk

Issue July 2013 ©Copyright 2013 - Eco-FX Limited